

Any point between 240 kHz and 600 kHz inclusive attenuated to a lower dB level of the unmodulated carrier than the 6 listed above: *No*

All points between 240 kHz and 600 kHz inclusive attenuated at least 35 dB below the level of the unmodulated carrier: *Yes*

3. Greater than 600 kHz from the carrier:

Based on the formula in 73.317(d) and a TPO of .245 Kw the minimum attenuation level is 67 dB.

700 kHz - 76 dB below the level of the unmodulated carrier
800 kHz - 76 dB below the level of the unmodulated carrier
1 MHz - 76 dB below the level of the unmodulated carrier
1.5 MHz - 76 dB below the level of the unmodulated carrier
2 MHz - 76 dB below the level of the unmodulated carrier
3 MHz - 76 dB below the level of the unmodulated carrier
5 MHz - 76 dB below the level of the unmodulated carrier
6 MHz - 76 dB below the level of the unmodulated carrier

Any point greater than 600 kHz from the carrier attenuated to a lower dB level of the unmodulated carrier than the 8 listed above: *No*

All points greater than 600 kHz from the carrier attenuated at least 76 dB below the level of the unmodulated carrier:

Comments: Scanned all points between 88.1 to 107.9 mhz and did not find any spurious emissions. The transmitter appears to be in good working order.

4. Preemphasis Set At: 75 μ sec

James L Travis